

PolyDome Feed Carts



Standard Features:

- Made from heavy duty, U.V. stabilized polyethylene
- High impact strength, even at low temperatures
- Easy cleaning—slick, smooth surface with no ribs, or seams
- Rounded bottom design for faster unloading or dumping
- Resists silage acids, feed additives, and other chemicals

PolyDome Feed Carts are built tough to give years of dependable service. Our feed carts are constructed of heavy duty polyethylene to resist dents and punctures and won't rust or corrode. They can withstand rough use; and yet are light enough for easy handling. Ultra-smooth, seamless bodies with no corners mean less chance of bacterial growth and easy cleaning. Rounded bottoms allow for easier dumping and unloading.

PolyDome Feed Cart Wheel Assemblies feature all-welded, bolted-on **steel frames** for solid support and durability. Large wheels include smooth-rolling bearings and semi-pneumatic tires. Front wheels are mounted on ball-bearing swivels for full, 360° rotation. All bolts, nuts and washers are included for easy installation.

5 Sizes available: 7, 12, 14, 15 and 20 Bushel Capacity



12 Bushel Feed Cart

PolyDome Feed Carts



15 Bushel Feed Cart

Specifications

	Model 7	Model 12	Model 14	Model 15	Model 20
Bushel Capacity	7	12	14	15	20
Outside Dimensions	44"x24"	50"x30"	56"x32"	56.5"x29.5"	67"x33"
Depth of Hopper	24"	24"	24"	16.5"	24"
When used with our wheel assembly					
No. of Wheels	4	4	4	4	4
Tires	8x2.50	10x3.50	10x3.50	10x3.50	10x3.50
Overall Height	36"	37"	37"	42"	37"
Load Rating	400 lbs.	500 lbs.	600 lbs.	600 lbs.	800 lbs.



14 Bushel

20 Bushel

7 Bushel

12 Bushel